


Scope: This specification applies to 12V POWER CABLE, WH-VG208-500-02.

General Specification


Items		Specification	Measurement condition, etc.
Environment	Operation temp.	0 to 70°C	Temp. gradient 15°C/H
	Storage temp.	-25 to 70°C	Temp. gradient 15°C/H
	Relative humidity	10 to 95%	No condensation
Others	Warranty	1 year after delivery. If any defects belong to us, the defective unit shall be repaired or replaced at our cost.	Provided that the unit shall be operated under normal temp. and humidity, and rating.
	For environment	RoHS compliant	

Rated current, Shape, dimension, etc.



CN	CONNECTOR TYPE	PIN No.	MAX CURRENT	FUNCTION	WIRE		PIN No.	CN	CONNECTOR TYPE
					COLOR	TYPE			
P1	Housing: CP-01108030 (CviLux) Terminal: 1,5PIN CP-01100102 (CviLux) Other CP-01100105 (CviLux) or equivalent	1	5.6A	COM	BLACK	UL1007 AWG #18	1	P2	Housing: CP-01108030 (CviLux) Terminal: CP-01100102 (CviLux) or equivalent
		2	5.6A	COM	BLACK		2		
		3	5.6A	COM	BLACK		3		
		4	5.6A	COM	BLACK		4		
		5	5.6A	+12V	YELLOW		5		
		6	5.6A	+12V	YELLOW		6		
		7	5.6A	+12V	YELLOW		7		
		8	5.6A	+12V	YELLOW		8		
		8	5.6A	+12V	YELLOW		1	P3	Housing: 45559-0002 (Molex) Terminal: 5556 (Molex)
		7	5.6A	+12V	YELLOW		2		
		6	5.6A	+12V	YELLOW		3		
		4	5.6A	COM	BLACK		4		
		3	5.6A	COM	BLACK		5		
		2	5.6A	COM	BLACK		6		

Note About Packaging
Output harness shall be packed in plastic bag with model label, and packed in a box separately with power supply unit.



Due to the technical improvement, the specifications and functions are subject to change without notice.

Drawn by	Yodo	Checked by		Approved by		Model:	WH-VG208-500-02	Drawing No.	6150-23-4-520
----------	------	------------	--	-------------	--	--------	-----------------	-------------	---------------