

Removable output harness WH-S0603-500




| Model | Stock | | | | | |
|---|----------------|---|---|---|------------------------|--------------------------------|
| WH-S0603-500 | Standard stock | | | | | |
| Model name coding WH - S 06 03 - 500 | | | | | | |
| ① | ② | ③ | ④ | ⑤ | ① Series name | ④ 3 pins for power supply side |
| | | | | | ② for signals | ⑤ Harness length (mm) |
| | | | | | ③ 6 pins for load side | |

Applicable power supply

| Desktop PC power supply | | System rack power supply | |
|-------------------------|-------|--------------------------|--------|
| Model | Page | Model | Page |
| ePCSA-650P-E2S | B-E2 | PC1U-300P-E2S | B-E206 |
| ePCSA-600P-E2S | B-E12 | | |
| PCSF-350P-X2S | B-E96 | | |

Dimension



Pinout assignment

| CONNECTOR TYPE | PIN No. | PIN No. | MAX CURRENT | WIRE COLOR | WIRE TYPE | CONNECTOR TYPE |
|---|---------|---------|-------------|------------|-----------|---|
| CN5 Housing: XAP-03V-1(JST) or equivalent Terminal: SXA-01T-P0.6(JST) or equivalent | 1 | 1 | 1.6A | WHITE | UL1007 | Housing: 5557-06R(Molex) or CP-01106030(CvILux) or equivalent Terminal: 5556(Molex) or CP-01100102(CvILux) or equivalent |
| | 3 | 2 | 1.6A | BLUE | AWG#22 | |
| | 2 | 3 | | N.C. | | |
| | - | 4 | | N.C. | | |
| | - | 5 | | N.C. | | |
| | - | 6 | | N.C. | | |

Product specification

| Items | Specification | Measurement condition |
|-------------|-------------------|---|
| Environment | Operating Temp. | -10 to 70°C |
| | Storage Temp. | -25 to 70°C |
| | Relative humidity | 10 to 95% |
| Others | Warranty | One year after delivery. However, if any faults belong to us, the defective unit shall be repaired or replaced at our cost. |
| | | Provided that the unit shall be operated under normal temp. and humidity, and rating. |