
Power harness for pattery backage connection WH-02VH02VH-250



Dimension



Product specification

Items		Specification	Measurement condition	
Env	Operating Temp.	-10 to 70°C	Temperature gradient 15°C/H	
ironn	Operating Temp. -10 to 70°C Storage Temp. -25 to 70°C Relative humidity 10 to 95%		Temperature gradient 15°C/H	
nent	Relative humidity	10 to 95%	No condensation	
Others	Warranty	One year after delivery. However, if any faults belong to us, the defective unit shall be repaired or replaced at our cost.	Provided that the unit shall be operated under normal temp. and humidity, and rating.	

Model		Stock		
WH-02VH02	2VH-250	Standard stock		
■ Model name co WH - 02V ① ②		① Series name ② 2-pin VH connector for battery package side ③ 2-pin VH connector for power supply side ④ Harness length (mm)		

Applicable power supply

System rack power supply					
Model	Page	Model	Page		
PCFL-180P-X2S2	B-E178	PCFD-180P-X2S	B-E188		

Applicable battery package

Model	Page	
BS17A-H24/2.0L	B-G8	

Pinout assignment

I	CONNECTOR TYPE	PIN No.	FUNCTION	WIRE COLOR	WIRE TYPE
I	Housing: VHR-2N(JST) or equivalent	1	BATT+	RED	UL1007
T	Terminal: SVH-41T-P1.1(JST) or equivalent	2	BATT-	BLACK	AWG#16